

LITHOPHANE-LIKE ARTICLE AND METHOD OF MANUFACTURE

In the late nineteenth and early twentieth centuries, lithophanes were formed from porcelain.

5 These objects were pieces of porcelain which were formed with sections of various thickness. The porcelain was fired at a very high temperature, resulting in the porcelain becoming translucent. By shining light through the porcelain from behind, as a result of the
10 different thicknesses of the porcelain and therefore the different transmissivity of light through the porcelain, an image is seen. In particular, the thicker areas of the porcelain are less transmissive to light than thinner areas, and so appear darker.

15

In the early part of the twentieth century, lithophanes were formed by hand engraving wax with the relief corresponding to the areas of different brightness of the desired image. These wax models were
20 used to form a mould which could be used to mould ceramic to form the lithophane. Such lithophanes were used as window hangings, fire screens, teapot warmers and lamps.

25 From around the 1930's, there was no longer any great interest in lithophanes, and they are rarely seen today.

The present invention relates to an article
30 having different thicknesses corresponding to the different intensities of an image, and to a method of forming such an article, the resulting article having a similar appearance to a porcelain lithophane.

35 According to a first aspect of the present invention, a method of forming an article comprises the steps of:

determining the relative intensity at different points of an image; and

forming the article with different thicknesses corresponding to the different intensities of the original image from a translucent material.

In accordance with the present invention, it is possible to replicate a desired image, for example a photograph or computer generated image, into an article such that the image can be observed with suitable lighting. This is possible by virtue of the step of determining the relative intensity of different points of the original image and the automatic use of this to form the final article with a variable thickness corresponding to the relative intensities. This differs from lithophanes which were generated as works of art in their own right.

It is preferred that the determination of the relative intensity of the different points of the image is achieved by scanning the image, for example into a computer. In this case, the original image may be divided into a number of picture elements, and an intensity value for each element determined. The intensity values are then preferably stored in memory for subsequent use in forming the article. In this way, the original image can accurately be recreated in the article. By storing the intensity values in a memory, it is possible to process the values, for example to normalise these, or vary these for different materials. It is also possible to enlarge or reduce the image, or to edit the image, for example by deleting parts of the image or combining images.

It is preferred that the step of forming the article comprises the step of forming a mould, and moulding the article in the mould. By moulding the article, for example by injection moulding techniques,

mass reproduction is possible. This allows the production of large volumes of product at a low cost, and this in turn increases the number of uses for the article.

5

Preferably the step of forming the mould is carried out by a numerically controlled engraving machine, such as a high speed three axis numerically controlled engraving machine. This can be loaded with
10 the relative intensity values of the desired mould, and can cut any desired number of moulds. If a non-flat article is to be produced, a four or five axis numerically controlled engraving machine may be needed.

Alternatively, the mould may be formed by a laser
15 cutting machine, by spark erosion in which a spark erosion electrode having a relief corresponding to the finished article is formed and is used to form the mould, or by stereo lithography or other techniques. The use of these methods for forming the mould are
20 especially suited to a method in which the data representing the relative intensity of the picture elements is held in a digital memory. In this case, the data can be used directly for defining, for example, the cutter toolpaths or the stereo lithography. This allows
25 for the rapid, reproducible and accurate formation of moulds for use in producing the finished articles. The accuracy allows greater detail to be seen in the finished article.

30 The mould is preferably formed from metal. This allows materials to be moulded which are heated to a high temperature to melt the material before being cooled to set. Such a mould may also have a long life to allow for repeated mouldings. Alternatively, the
35 mould may be a flexible mould, for example formed of rubber or polyethane. This is especially suitable where the article is made from a fragile material, as it allows the article to be removed from the mould easily,

for example by peeling off the mould, without damaging the article.

It is preferred that a number of moulds are formed from a single mould block to allow a large number of articles to be moulded simultaneously.

In an alternative example of the present invention, the article is formed by machining or otherwise forming the article directly from a translucent material based on the determined relative intensity so that the article has a relief such that the thickness corresponds to the different intensities of the desired image.

This method of forming articles does not allow for the same economy of scale and mass reproduction associated with moulding, but is able to produce limited quantities of articles having a specific design. For example, a person's image can be obtained from a digital camera or from a scanned photograph, and machined into an article. This will be difficult to replicate, and so can be used as a security or identification device.

The article may be formed by a number of methods, including those described above for the forming of a mould, including engraving by a numerically controlled engraving machine, by laser cutting, spark erosion or stereo lithography.

In a further example, the determined relative intensity data is used to form a die, punch or stamp. The die, punch or stamp, as with the mould, may be formed by machining, such as by a numerically controlled engraving machine, by laser cutting, spark erosion or by stereo lithography. To form the article, the die, punch or stamp is pressed onto the surface of the material from which the article is to be formed, and leaves an

imprint in the material, giving the desired thickness variation for the article. Depending on the material used to form the article, the punch, die or stamp may be heated prior to being pressed into the material. These 5 techniques are particularly suitable for the formation of articles in which a moulding step is difficult in the context of the normal production process.

A material which is especially suitable for 10 stamping is chewing gum which is usually formed in strips that are cut to size. The stamping of a relief in a strip of chewing gum can be linked with the cutting of the strip to the required size. Especially where the article is formed in a strip, the punch, die or stamp 15 may be provided on a roller.

Preferred materials from which the article may be formed include plastics, confectionery products including chewing gum, candy and chocolate, wax, soap 20 and liquids.

A particularly preferred material is plastics. Such an article is advantageous over a porcelain lithophane in that it is significantly cheaper and 25 easier to manufacture, does not require firing at a high temperature and is less susceptible to damage. Further, by selection of a suitable material, it is possible to see the image clearly when the article is back lit by a particular type or intensity light source.

30

In the case of liquid, the liquid may remain in the mould to maintain the different thicknesses.

According to an alternative example of the 35 present application, there is provided a plastics article having different thicknesses at different positions corresponding to the relative intensity of an image, in which the plastics article transmits or emits

light with an intensity corresponding to the thickness of the material.

The material from which the plastics articles
5 are formed should be transparent or translucent, for example may be polystyrene, polypropylene, styrolux, ABS or acrylic or an epoxy, polystyrene or polyurethane resin. The plastics material is preferably filled with a filler material such as china clay, chalk or other
10 filter to give the desired effect.

The use of plastics is preferred since this is inexpensive, can be formed to the desired shape easily, for example by heating to make the material mouldable
15 and cooling to set, and is resilient, making it less likely to break than porcelain. Plastics materials may also be used for a wide range of products for use in a large number and variety of environments.

20 Alternative materials from which the article may be formed include confectionery products, wax, soap and liquid.

Where confectionery products, for example
25 chocolate, candy or chewing gum, is used, the finished articles can be eaten. As many confectionery products are shaped to give desirable appearance, little if any additional cost is required to form the product into an article in accordance with the present invention, but
30 the resulting article has a very attractive appearance, increasing its value.

Where the article is formed from liquid, it is preferred that the article comprises a container formed
35 from substantially transparent material in which the cross-sectional area between opposite walls corresponds to the relative intensity of the image, and liquid provided in the container. The container may be in the

form of a bottle. The liquid may be a beverage or detergent or cosmetic, such as shampoo. To give the desired effect, the liquid should preferably be of uniform density and transmissivity, and should be
5 translucent.

The material from which the article is formed may include luminescent particles or may be coated on the back by a luminescent layer. In this case, the
10 luminescent particles emit light, and it may therefore be possible to view the image without light from a separate source being shone through the article. Where luminescent particles are included, the lighter parts of the image may correspond to the thicker parts of the
15 article and the darker parts to the thinner parts as, in this case, in the thicker regions there will be a greater amount of luminous particles and therefore there will be a brighter section.

20 The article may be coloured. In this case, the article may be coloured with a single colour to give an overall tint, or there may be different colours at different parts of the article to give parts of different colour.

25

Where the colour is a single colour, this may be achieved by including pigment in the material used for the moulding. Alternatively, a coloured layer may be formed on a surface of the article. One surface of
30 the article, for example the rear surface, will usually be planar, and therefore a coloured layer can be formed on this surface easily, for example by transfer or sublimation printing or by an ink jet or silk screen printing technique. This will act as a filter to the
35 light passing through the article. Alternatively, a separate layer may be provided with the appropriate colours which is provided behind or in front of the

article. This allows the colour to be formed separately.

The article may be formed from heat sensitive material. In this case, the image may only be seen when the article is heated. For example, if the article is formed into a lamp shade, it may be heated by the lamp to become translucent.

10 The article according to the present invention can be used for a number of purposes, including character promotions, key rings, inserts to be provided in cereal packets, light shades, plates, cups, toys, pictures etc. Where the article is made from an edible
15 material, such as chocolate or candy, the article may be sold as a novelty food item. A candle can be formed where the article is made from wax.

By use of suitable processing techniques, the
20 article may be a non-flat or three-dimensional article. It is also possible to produce a stereoscopic image by having two side by side articles having substantially the same image but from a slightly different perspective, each of the images being viewed by a
25 different one of the viewer's eyes.

In an alternative example, both surfaces of the article include relief. In this case, the overall thickness of the material at any point corresponds to
30 the relative intensity of the image at that point, however the article is recessed on both sides. This gives an article which can be viewed from either side. Where the article includes one flat surface and the relief is provided exclusively in the other surface, the
35 image can only be viewed properly from the relieved side of the article. Where both surfaces of the article include relief, it is preferred that the article is recessed on both sides to a generally similar amount.

This eases the manufacture of the article. For example, where the article is formed in a mould, the two parts of the mould may be engraved as a mirror image of each other.

5

The article may be formed as a single piece, or may be formed in two parts which are fixed back-to-back. Where the article is formed in two parts and these are fixed back-to-back, such fixing may be by means of an adhesive, or may be by a mechanical interconnection or clamp. Where the article is formed in two parts, it is possible to provide a coloured or luminescent layer between the two parts before these are assembled together to give the desired colour filter or radiation of light as required.

Examples of the present invention will be described in accordance with the accompanying drawings, in which:

20 Figure 1 shows a schematic view of the system for forming an article;

Figure 2 shows a cross-section through a mould for forming an article;

Figure 3 shows a cross-section through an alternative example of an article; and,

Figure 4 shows a bottle of liquid including the features of the present invention.

As shown in Figure 1, an image 1, for example a photograph or painting, is scanned by a scanner 2 to convert the image 1 into electronic data which corresponds to the image 1. The data corresponding to the scanned image is input to a processor 3. Alternatively, the image may be generated initially in electronic form, for example using a graphics package, or may be loaded from a store of pre-converted or generated images, for example from a CD-ROM, or downloaded, for example from the Internet.

The processor 3 analyses the data corresponding to the image to determine the relative intensity, i.e. the relative darkness or lightness, at 5 different points or pixels of the image. This analysis may be achieved using commercially available computer aided design or computer aided milling software. This intensity information is provided to a numerically controlled milling machine from the software which is 10 able to use the intensity data to machine one half 11 of a mould in which the depth of the mould at different positions corresponds to the relative intensities of the original image. In a preferred example, the mould has a greater depth where the corresponding position of the 15 original image has a low intensity (i.e. where the image is dark), and has a shallower depth where the corresponding position of the original image has a high density (i.e. where the image is light).

20 The machined mould half 11 and an associated mould half 10 having a generally flat surface, are placed together to form a mould cavity, and plastics material is injected into the mould cavity. To give the plastics material the required translucent properties, a 25 filler material such as china clay, chalk or other filter material is added to the plastics before this is injected into the mould cavity.

When the plastics material has set, it is 30 removed from the mould. The resulting article will be translucent, and will have a greater thickness in those areas corresponding to darker areas of the original image than the areas corresponding to the lighter areas of the original image. When light is shone through the 35 article from behind, the light is transmitted through the thinner parts of the article more easily than through the thicker parts of the article, and therefore the thinner areas appear lighter than the thicker areas.

This corresponds generally to the light and dark areas of the original image, and therefore an image corresponding to the original image can be seen.

5 The article may be coloured on the back by any suitable printing technique, for example by ink jet printing. In this case, the colour is easy to apply as it is applied to the flat rear surface of the article. The coloured layer on the back of the article acts as a
10 colour filter which only lets light of selected wavelengths pass through the layer and hence through the translucent article, and therefore the light viewed through the article is of certain colours. Where the rear of the article is coloured substantially entirely
15 with a single colour, the whole image viewed through the article will have a colour tint, however it is preferred that the rear of the article is selectively coloured with areas of different colour. This allows the light transmitted through different parts of the article to be
20 of different colours, which may correspond to the colours of the original image.

 Alternatively, a coloured pigment may be added to the plastics material before this is injected into
25 the mould. In this case, the pigment within the plastics material will act as a filter to allow only light of certain wavelengths to be transmitted to form the view image.

30 It is also possible to add a luminescent pigment to the plastics material used to injection mould the article. In this case, it is not necessary for a separate back light to be used to view the article, since the article will itself emit light. In this case,
35 the mould is made in reverse to that described above, with the areas corresponding to the lighter sections of the image being formed more deeply than the areas corresponding to the darker areas. In this case, the

plastics article moulded by the mould will be thicker in those areas corresponding to lighter areas of the original image, and therefore will have a greater amount of luminescent pigment, and therefore will emit more light than the thinner areas corresponding to the darker regions of the original image which will have less luminescent material and therefore will emit less light.

An alternative example of an article according to the present invention is shown in cross-section in Figure 3. In this example, rather than the article being formed with a flat rear surface and a front surface having a relief corresponding to the relative intensity of the different parts of the image, the article is formed with a corresponding relief on both faces. This can be achieved either by forming the two mould halves with a corresponding, mirror image, relief, the relief in each part corresponding to half the required relief for the desired overall thickness of the finished product, or by engraving with a CNC machine. Alternatively, as shown in the example of Figure 3, the article can be formed in two parts, each part having one flat face and one face with relief, each part made in accordance with any of the methods described herein.

In this case, the two parts of the article are fixed together in back-to-back relation. Due to the variation in thickness of the complete article, there will be a similar transmission of light as with a single article having a flat rear face. However, it is possible to view the image through the article from either side, whereas when one face is flat, it is difficult to view the image from this flat face.

As shown in Figure 3, a coloured layer is printed on the flat face of one part of the article. In the complete article, this layer is sandwiched between the two parts of the article and therefore is not

susceptible to damage, for example by wear or scratching. The coloured layer may alternatively or additionally be a luminous layer, in which case it may not be necessary to hold the article to a light source when the image is viewed. The two parts of the article are then joined by a suitable adhesive.

As with the first example, it is possible to provide a coloured or luminescent layer on one face of the article, or to make the article of a plastics material including coloured or luminescent particles.

The injection moulded articles according to the present invention, which, due to the method of manufacture can be formed inexpensively and in large numbers, can be used in many different applications, for example, but not limited to, character promotions, key rings, inserts to be provided in cereal packets, light shades, plates, cups, and pictures.

It may also be possible to form a plastics article having variable thickness or contour corresponding to the relative intensity of an original image by engraving the article directly, for example using a CNC machine, in the same way as described above for forming the mould. In this case, it would be simple to make one-off items, for example it would be possible to convert an image of a person's face into data relating to the relative intensity of the image, and directly engrave a plastics article with different thickness regions corresponding to the different intensities of the image of the person's face. This could be used as a security device, for example as an identification card, which would be very difficult to forge.

In an alternative example, a bottle is formed of transparent material in which the width of the bottle

varies to correspond to the relative intensity of an image. When the bottle is filled with liquid, the amount of liquid will correspond to the relative intensity of the original image. Where the liquid is
5 translucent, this variation in the amount of liquid will give darker and lighter regions. A cross-section of a bottle is shown in Figure 4.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227